

Specification for Axminster Tile (AXT) 3ply – 9row - 740 Tex

Construction:	Woven Axminster – Electronic Jacquard
Yarn Content:	80% Premium Grade Virgin Wool / 20% Nylon
Twist Coefficient:	3 ply 740 tex
Dye Method:	Skein Dyed
Weft:	Polypropylene
Warp:	Cotton / PET Polyester
Secondary Backing:	Cushion Back

	Imperial	Metric
Yarn Ply:	3 ply – 3/42	3 ply – 4050/3
Rows per Inch:	9 per inch	35.43 per DM
Pitch per Inch:	7 per inch	27.56 per DM
Pile Height:	0.280"	7.0mm
Total Thickness:	0.52"	13.2mm
Effective Pile Weight:	31.3oz/yd ²	1060 gr/m ²
Total Pile Weight:	40oz/yd ²	1356gr/m ²
Tile Size:	35.43" x 35.43"	90 cms x 90 cms

Performance

Color Fastness (light):	ISO 105 - B02 ≥ 5
Color Fastness (rubbing):	ISO 105 - X12 ≥ 3
Tuft Withdrawal Force:	ISO 4919 ≥ 10N
TARR:	ISO 10361 ≥ 3
Anti-Static:	ISO 6356 ≥ 2Kv
Flammability:	ASTM E - 648 Radiant Flux: Class 1 EN13501-1 -Class cfl -sl

All specifications subject to normal manufacturing tolerances.

Encore Hospitality flooring products are to be installed in full accordance with Encore’s installation instructions and standard trade practices. A program of regular cleaning and maintenance is vital for retaining a high appearance level. Installation plus Care & Maintenance manuals can be downloaded at www.encorehospitalitycarpet.com